

You journey the world to find it; the place where serenity joins exploration. Where the sea meets the sand and the cliffs meet the clouds, you find an untouched path that sparks transformation.

Tommy Bahama® calls this living the island life. The brand invites you to a place without deadlines or demands, to enjoy simple pleasures, and to live spontaneously — all while breathing freely and relaxing in style.

Lunada Bay Tile is pleased to partner with Tommy Bahama® to create a premier collection of tile. An exquisite collection of handcrafted glass tile blends inspired by the most exotic and untouched destinations of the world.

Please visit [LunadaBayTile.com](http://LunadaBayTile.com) for our complete product offerings, applications and installation instructions.



Tommy Bahama® by **LUNADA BAY TILE**

Up to 70% post-consumer recycled glass content ♻️

© 2020 Lunada Bay Tile. All Rights Reserved

RECOMMENDED USAGE		FLOOR APPLICATIONS		
Application	Suitable		Interior	Exterior
Interior Wall/Backsplash	Yes	Shower	Yes	Yes **
Fireplace/Cooktop Surround	Yes *	Steam Shower	Yes **	N/A
Shower Wall	Yes	Light Residential	Yes	No
Steam Shower	Yes **	Residential	Yes	No
Exterior Wall	Yes	DCOF Value of ≥ 0.42 is accepted value for use in commercial applications. A 137.1-2018		
Pool, Spa or Water Feature (fully submerged)	Yes **			

PRODUCT SPECS			TESTING		
Size (Dimension In Nominal Size)	Coverage (SF Per Sheet)	Packaging (Per Box)			
1 x 1" Offset	1.07	5 Sheets/5.35 SF	Breaking Strength	ASTM C-648	> 350 PSI
1 x 2" Brick	1.00	5 Sheets/5.00 SF	Water Absorption	ASTM C-373	Impervious ≤ 0.5%
1/2 x 4" Brick	0.84	5 Sheets/4.20 SF	Chemical Resistance	ASTM C-650	Unaffected
1 x 4" Brick	0.85	5 Sheets/4.25 SF	Freeze/Thaw	ASTM C-1026	Unaffected
Vineyard	0.82	5 Sheets/4.10 SF	Thermal Shock	ASTM C-483	Passed
Zig & Zag	0.74	5 Sheets/3.70 SF			

Shade Variation	Grout Joint Recommendation
V4 - Substantial Variation	1/16" (1.6 mm)

**NOTES**

Since variations are common in artistic glass tile, we recommend final selection be made from an actual tile mock-up. To achieve optimal results in shading, layout and design, tile should be randomly selected from multiple boxes during installation. We recommend a minimum of 10% overage on all orders. **Installation constitutes acceptance.** We advise retaining control samples to aid in color matching if additional material is required (match not guaranteed).

**MAINTENANCE**

A routine cleaning of Tommy Bahama Glass tiles can be done with light duty, diluted close to neutral pH cleaner.

\* Acceptable for use near open flame or heat source; however, it is not considered 'Fire Glass'.  
 \*\* ACCEPTABLE SIZES: 1 x 1", 1 x 2", and Vineyard Only. No other sizes are recommended.

**FLOOR APPLICATION DEFINITIONS:**  
**Light Residential** - Flooring areas subject to soft-soled footwear or normal footwear traffic without abrasive soil/dirt, such as bathrooms and bedrooms without exterior access and minimal pivot points.  
**Residential** - Flooring areas subject to soft-soled or normal footwear traffic that may contain amounts of abrasive soil/dirt, such as living rooms, dining rooms or other rooms with exterior access.