## Contourz

A specially designed mix of engineering and craftmanship deliver Contourz concrete tiles in a variety of serene colors and modern shapes with three-dimensional or flat surfaces. The concrete tiles deliver expressive, architectural sculpture that blends art, industry and elegance. Custom colors are also available.



Please visit LunadaBayTile.com for our complete product offerings, applications and installation instructions.

© 2023 Lunada Bay Tile. All Rights Reserved

				© 2025 Lundud Day The. All Rights Reserved				
RECOMMENDED USAGE				FLOOR APPLICATIONS				
Application			Suitable			Interior		Exterior
Interior Wall/Backsplash		Yes	Shower		No		No	
Fireplace/Cooktop Surround			Yes *	Steam Shower		No		N/A
Shower Wall			Yes	Light Residential		Yes		No
Steam Shower			Yes	Residential		No		No
Exterior Wall			Yes					
Pool, Spa or Water Feature (fully submerged) Yes **								
PRODUCT SPECS				TESTING				
Size Coverage (Dimension In Nominal Size) (SF Per Piece)			Packaging (Per Box)	Standards Methods				
3 x 9″	5.71	15	5 Pieces/2.627 SF	Breaking Strength	A	ASTM C-648		>16000 PSI
4" Hex	10.95	5	2 Pieces/4.749 SF	Water Absorption	A	ASTM C-373	Vitreous ≥ .05% -≤ 3.0%	
6 x 9″	2.82	1	5 Pieces/5.319 SF	Chemical Resistance	A	ASTM C-650	Pass	
Fanfare Hex (4")	10.95	2	8 Pieces/2.557 SF	Freeze/Thaw	Д	STM C-1026		Unaffected
In & Out (2 ½ x 9")			12 Pieces/Box	Warpage	A	ASTM C-485		± 0.26%/± 1.5mm
<b>Retro Curve</b> (1 ½ x 9")			18 Pieces/Box	NOTES				
<b>Trifecta</b> (9 x 10 ¼")	3.15	e	6 Pieces/1.905 SF					
Zen Break A (3 × 9")	5.71         16 Pieces/2.802 SF           5.71         16 Pieces/2.802 SF			Since variations are common in artistic concrete tile, we recommend final selection be made from an actual tile mock-up. To achieve optimal results in shading, layout and design, tile should be randomly selected				
Zen Break B (3 × 9")								
Shade Variation Grout Joint Recommendation				from multiple boxes during installation. We recommend a minimum of 10% overage on all orders. On dimensional patterns, using a grout bag is				
V2 - Slight Variation 1/8" (3 mm)				the best method to target competent and successful grout application. Grout floats should not be used due to the luster glaze. please take care when grouting and protect surface from abrasion. <b>Installation</b> <b>constitutes acceptance</b> . We advise retaining control samples to aid in color matching if additional material is required (match not guaranteed). Contourz has similar characteristics and care requirements as natural stone (marble or limestone).				
				MAINTENANCE				
				A routine cleaning of <b>Contourz</b> tile can be done with a light duty non- abrasive, close to neutral pH detergent cleaner.				
<ul> <li>Acceptable for limited and sporadic exposure near open flame or heat source, including fireplace wall/cooktop surround. NOT recommended for placement inside a firebox.</li> <li>Contourz Tile will need to be sealed on-site with a product that is recommended by the specifier or a specific sealer manufacturer. Sealers used in Pool/Spa applications should be chemically resistant and UV stable. Please check with the sealer manufacturer prior to application for suitability.</li> </ul>				<ul> <li>FLOOR APPLICATION DEFINITIONS:</li> <li>Light Residential - Flooring areas subject to soft-soled footwear or normal footwear traffic without abrasive soil/dirt, such as bathrooms and bedrooms without exterior access and minimal pivot points.</li> <li>Residential - Flooring areas subject to soft-soled or normal footwear traffic that may contain amounts of abrasive soil/dirt, such as living rooms, dining rooms or other rooms with exterior access.</li> </ul>				