

Graphite

Artists throughout the centuries have used charcoal for sketching outlines of their frescos and creating illustrated masterpieces. This art medium is inspiration for Graphite, a handcrafted ceramic series offering an expanding variety of options for personal expression. From subtly textured charcoal surfaces to metallic bronze, and colorful artistic pigments – the juxtaposition of color, light, and shadow evokes emotion, drama, and contemplation.



SCAN CODE FOR MORE INFORMATION ON THE GRAPHITE COLLECTION



Up To 45% Post-Consumer Recycled Content

Please visit LunadaBayTile.com for our complete product offerings, applications and installation instructions.

© 2023 Lunada Bay Tile. All Rights Reserved

RECOMMENDED USAGE			FLOOR APPLICATIONS		
Application		Suitable		Interior	Exterior
Interior Wall/Backsplash		Yes	Shower	No	No
Fireplace/Cooktop Surround		Yes *	Steam Shower	No	N/A
Shower Wall		Yes	Light Residential	Yes	No
Steam Shower		Yes	Residential	No	No
Exterior Wall		Yes **	<i>DCOF Value of ≥ 0.42 is accepted value for use in commercial applications. A 137.1-2018</i>		
Pool, Spa or Water Feature (fully submerged)		Yes ▲			
PRODUCT SPECS			TESTING		
Size (Dimension In Nominal Size)	Coverage (SF Per Piece)	Packaging (Per Box)	Standards Methods		
4" Hex	0.090	44 Pieces/3.939 SF	Breaking Strength	ASTM C-648	> 450 PSI
2 ½ x 9 ½"	0.155	32 Pieces/4.960 SF	Water Absorption	ASTM C-373	Vitreous ≥ 0.5% - ≤ 3.0%
3 ½ x 9 ½"	0.233	20 Pieces/4.660 SF	Chemical Resistance	ASTM C-650	Unaffected
4 ¾ x 9 ½"	0.310	16 Pieces/4.960 SF	Freeze/Thaw	ASTM C-1026	Unaffected
Duet (1 ¼ - 3 ½ x 9 ½")	0.155	32 Pieces/4.960 SF	Warpage	ASTM C-485	± 0.26% /± 1.5mm
Liner (¾ x 9 ½")	1.27 LF/PC	80 Pieces/101.60 LF	NOTES Since variations are common in artistic ceramic tile, we recommend final selection be made from an actual tile mock-up. To achieve optimal results in shading, layout and design, tile should be randomly selected from multiple boxes during installation. We recommend a minimum of 10% overage on all orders. Please take care when grouting and protect surface from abrasion. Installation constitutes acceptance. We advise retaining control samples to aid in color matching if additional material is required (match not guaranteed). It is critical to consider sealing the Graphite series tile for all applications. Sealers may effect the appearance of the tile and therefore it's best to receive professional advice from a qualified source prior to application. We strongly encourage a test is performed and accepted by the owner/owners prior to complete application of the assembly.		
Shade Variation	Grout Joint Recommendation				
V1 - V2 Slight Variation	1/8" (3 mm)				
			MAINTENANCE		
			A routine cleaning of Graphite tile can be done with a light duty non-abrasive, close to neutral pH detergent cleaner.		

* Acceptable for limited and sporadic exposure near open flame or heat source, including fireplace wall/cooktop surround. **NOT** recommended for placement inside a firebox.

** When Graphite series tile is to be placed in an exterior application, it is strongly recommended to seal the entire assembly after installation.

▲ Molten Bronze is **NOT** acceptable for use in a submerged or partially submerged application, such as a pool, spa, water feature. All other colors are acceptable.

FLOOR APPLICATION DEFINITIONS:

Light Residential - Flooring areas subject to soft-soled footwear or normal footwear traffic without abrasive soil/dirt, such as bathrooms and bedrooms without exterior access and minimal pivot points.

Residential - Flooring areas subject to soft-soled or normal footwear traffic that may contain amounts of abrasive soil/dirt, such as living rooms, dining rooms or other rooms with exterior access.