## JAW (Just Add Water)

JAW (Just Add Water) is an enticing series of glass tile borders for pool waterlines, showers, spas, water features and other border applications. Border heights can be increased with sheets of corresponding field material. Easy to use straight out of the box, and coordinate with LBT's Agate and Luce series.





Please visit LunadaBayTile.com for our complete product offerings, applications and installation instructions.

© 2024 Lunada Bay Tile. All Rights Reserved

FLOOR APPLICATIONS

Application			Suitable			Interior		Exterior
Interior Wall/Backsplash			Yes	Shower		Yes		Yes
Fireplace/Cooktop Surround			Yes *	Steam Shower		Yes		N/A
Shower Wall			Yes	Light Residential		Yes		No
Steam Shower			Yes	<b>Residential</b> No		No		No
Exterior Wall			Yes					
Pool, Spa or Water Feature (fully submerged)			Yes					
PRODUCT SPECS				TESTING				
Size (Sheet Size)	Coverage (Per Sheet)		Packaging (Per Box)	Standards Methods				
<b>2" Hex Border</b> (5.83 x 11.64")	0.975 LF/0.480 SF	5 Sheets/4.873 LF/2.398 SF		Breaking Strength	A	ASTM C-648		>350 PSI
2" Hex Field (11.76 x 11.64")	0.95 SF	5 Sheets/4.75 SF		Water Absorption	,	ASTM C-373	lm	pervious < 0.05%
Feather 6 Border (5.96 x 12.36")	1.03 LF/0.512 SF	5 Sheets/5.149 LF/2.560 SF		Chemical Resistance	A	ASTM C-650		Unaffected
Feather Field (10.24 x 9.92")	0.705 SF	5 Sheets/3.525 SF		Freeze/Thaw	A	ASTM C-1026		Unaffected
<b>Zing 1 x 3 Border</b> (5.51 x 9.96")	0.83 LF/0.381 SF	5 Sheets/4.150 LF/1.905 SF		Thermal Shock	A	ASTM C-484		Passed
<b>Zing 1 x 3 Field</b> (12.13 x 9.96")	0.839 SF	Ę	Sheets/4.195 SF	NOTES				
Shade Variation Grout Joint Recommendation  V3 - V4 Substantial Variation 1/16" (1.6mm)				Since variations are common in artistic glass tile, we recommend final selection be made from an actual tile mock-up. To achieve optimal results in shading, layout and design, tile should be randomly selected				
				results in stiduling, layou	t and	acsign, the shoul	u De	randonny selected

selection be made from an actual tile mock-up. To achieve optimal results in shading, layout and design, tile should be randomly selected from multiple boxes during installation. We recommend a minimum of 10% overage on all orders. Please take care when grouting and protect surface from abrasion. **Installation constitutes acceptance**. We advise retaining control samples to aid in color matching if additional material is required (match not guaranteed).

## **MAINTENANCE**

A routine cleaning of **JAW** tile can be done with a light duty non-abrasive, close to neutral pH detergent cleaner.

\* Acceptable for use near open flame or heat source; However it is NOT considered 'Fire Glass'.

RECOMMENDED USAGE

## FLOOR APPLICATION DEFINITIONS:

**Light Residential** - Flooring areas subject to soft-soled footwear or normal footwear traffic without abrasive soil/dirt, such as bathrooms and bedrooms without exterior access and minimal pivot points.

**Residential** - Flooring areas subject to soft-soled or normal footwear traffic that may contain amounts of abrasive soil/dirt, such as living rooms, dining rooms or other rooms with exterior access.