


Origami Mosaic

Lunada Bay Tile takes its first direct inspiration from the Japanese art of paper folding with Origami Mosaic glass tile. The techniques and visuals seen in the revered art form are reimagined in three-dimensional glass mosaics with delicate angles and subtle geometry.



Up To 70%
Post-Consumer
Recycled Content

Please visit LunadaBayTile.com for our complete product offerings, applications and installation instructions.

© 2021 Lunada Bay Tile. All Rights Reserved

RECOMMENDED USAGE			FLOOR APPLICATIONS		
Application	Suitable		Interior	Exterior	
Interior Wall/Backsplash	Yes		Shower	No	No **
Fireplace/Cooktop Surround	Yes *		Steam Shower	No	N/A
Shower Wall	Yes		Light Residential	No	No
Steam Shower	No		Residential	No	No
Exterior Wall	Yes **				
Pool, Spa or Water Feature (fully submerged)	No				
PRODUCT SPECS			TESTING		
Size (Dimension In Nominal Size)	Coverage (SF Per Sheet)	Packaging (Per Box)	Standards Methods		
Nami (1 x 1")	1.07	5 Sheets/5.35 SF	Breaking Strength	ASTM C-648	> 350 PSI
Sway (1" Hex)	1.08	5 Sheets/5.40 SF	Water Absorption	ASTM C-373	Impervious < 0.05%
Vesper (3/8 x 2")	1.04	5 Sheets/5.20 SF	Chemical Resistance	ASTM C-650	Unaffected
Vesper Twist (3/8 x 2")	1.04	5 Sheets/5.20 SF	Freeze/Thaw	ASTM C-1026	Unaffected
Shade Variation	Grout Joint Recommendation		Thermal Shock	ASTM C-484	Passed
V2 - V3 Moderate Variation	1/16" (1.6 mm)		NOTES		
			<p>Since variations are common in artistic glass tile, we recommend final selection be made from an actual tile mock-up. To achieve optimal results in shading, layout and design, tile should be randomly selected from multiple boxes during installation. We recommend a minimum of 10% overage on all orders. On dimensional patterns, using a grout bag is the best method to target competent and successful grout application. Grout floats should not be used due to the luster glaze. please take care when grouting and protect surface from abrasion. Installation constitutes acceptance. We advise retaining control samples to aid in color matching if additional material is required (match not guaranteed).</p>		
			<p>MAINTENANCE</p> <p>A routine cleaning of Origami Mosaic tile can be done with a light duty non-abrasive, close to neutral pH detergent cleaner.</p>		

* Acceptable for use near open flame or heat source; However it is **NOT** considered 'Fire Glass'.

** Origami Mosaic tiles are suitable for installation on interior walls or exterior shaded walls only. **NOT** suitable for installation in pools, spas and/or water features or steam showers. Origami Mosaic tile series is mesh mounted.

FLOOR APPLICATION DEFINITIONS:

Light Residential - Flooring areas subject to soft-soled footwear or normal footwear traffic without abrasive soil/dirt, such as bathrooms and bedrooms without exterior access and minimal pivot points.

Residential - Flooring areas subject to soft-soled or normal footwear traffic that may contain amounts of abrasive soil/dirt, such as living rooms, dining rooms or other rooms with exterior access.