Tomei Modules

Tomei Modules is a versatile collection of large-format glass tiles inspired by modern architectural masters. Created for residential and commercial walls, the large modular field tiles help you create tailored statements from gentle panoramas to bold and playful abstractions. Like an endless canvas, the nuanced colors are suggestive of misty fogs, budding leaves, and broadening horizons.



Please visit LunadaBayTile.com for our complete product offerings, applications and installation instructions. © 2019 Lunada Bay Tile. *All Rights Reserved*

RECOMMENDED USAGE				FLOOR APPLICATIONS				
Application			Suitable			Interior		Exterior
Interior Wall/Backsplash			Yes	Shower		No		No
Fireplace/Cooktop Surround			Yes *	Steam Shower		No		N/A
Shower Wall			Yes	Light Residential		No		No
Steam Shower			No	Residential		No		No
Exterior Wall			No		ceptec	value for use in commercial applications.		
Pool, Spa or Water Feature (fully submerged)			No	A 137.1-2018				
PRODUCT SPECS				TESTING				
Size (Dimension In Nominal Size)	Coverage (SF Per Piece)		Packaging (Per Box)	Standards Methods				
6 x 9" Piece	0.358	8	3 Pieces/2.87 SF	Breaking Strength	A	ASTM C-648		>650 PSI
6 x 12" Piece	0.478	6	6 Pieces/2.87 SF	Water Absorption	A	ASTM C-373	In	npervious<0.05%
9 x 18" Piece	1.08	4	4 Pieces/4.32 SF	Chemical Resistance	A	ASTM C-650		Unaffected
12 x 18" Piece	1.45	4	4 Pieces/5.80 SF	Freeze/Thaw	Д	STM C-1026		Unaffected
				Thermal Shock	A	ASTM C-484		Passed
Shade Variation Grout Joint Recom			nmendation	Thickness Drilling Holes				oles
V1 - V2 Slight Variation 1/8" (3 mm))	5/16" (8 mm)	5/16" (8 mm) 1/8"-3/16" (2-3 mm) WIDER			
				NOTES Since variations are common in artistic glass tile, we recommend final selection be made from an actual tile mock-up. To achieve optimal results in shading, layout and design, tile should be randomly selected from multiple boxes during installation. We recommend a minimum of 10% overage on all orders. Installation constitutes acceptance . We advise retaining control samples to aid in color matching if additional material is required (match not guaranteed).				
								A routine cleaning of To diluted close to neutral
 Acceptable for use near open flame or heat source; however, it is not considered a 'Fire Glass". 				FLOOR APPLICATION DEFINITIONS:Light Residential - Flooring areas subject to soft-soled footwear or normal footwear traffic without abrasive soil/dirt, such as bathrooms and bedrooms without exterior access and minimal pivot points.Residential - Flooring areas subject to soft-soled or normal footwear traffic that may contain amounts of abrasive soil/dirt, such as living rooms, dining rooms or other rooms with exterior access.				

l